

Part Numbering System

BD USA 273



INTERNAL RELIEF	
C	constant loaded

OPCO TYPE	
2	309LP OPCO
3	309LP UPCO/OPCO
4	309LP2 OPCO
5	309LP2 UPCO/OPCO
6	309LP4 OPCO
7	309LP4 UPCO/OPCO
X	None

CONNECTIONS SIZE	
H	1¼" x 1¼"
I	1¼" x 1½"
J	1¼" x 2"
K	1½" x 1½"
L	1½" x 2"
M	2" x 2"

CONNECTION TYPE	
N	NPT
B	BSPT
P	BSPP
6	PN16RF
7	PN16FF
1	ANSI 150RF
2	ANSI 150FF
5	274 valve head

MATERIAL	
D	Ductile Iron

IMPULSE	
I	Internal
E	External

OPTIONAL FEATURES*	
T	Stainless Steel Pilot Feed Line
I	Test Point on Inlet
O	Test Point on Outlet
E	Casting Engraving
B	Test Point on both Inlet & Outlet
F	Inlet Filter Strainer
Z	Blanking Plate
W	Safety Diaphragm
X	None

BODY/VENT ORIENTATION**	
E*	B1
M	D1

ORIFICE DIAMETER	
20.0mm	S
30.0mm	U

UPCO SPRING	
1138	A
638	B
IA/006	D
None	X

OPCO SPRING	
861	A
1171	F
1172	G
1173	H
1174	I
1175	J
1254	C
1030	K
1031	L
1032	M
1033	N
None	X

PILOT SPRING	
1047	6
TX/002	2
TX/003	3

*Optional features may be paired together in series.

**E is standard Body/Vent Orientation